

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
14 March 2002 (14.03.2002)

PCT

(10) International Publication Number
WO 02/20288 A1

(51) International Patent Classification⁷: **B60G 7/00, 9/00**

(21) International Application Number: **PCT/GB01/03895**

(22) International Filing Date: **31 August 2001 (31.08.2001)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
0021718.2 5 September 2000 (05.09.2000) **GB**

(71) Applicant (for all designated States except US): **MERITOR HEAVY VEHICLE SYSTEMS LIMITED**
[GB/GB]; Llay Industrial Estate, Rackery Lane, Llay,
Wrexham LL12 0PB (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **CHAN, David**

[GB/GB]; 4 The Larches, Hawarden, Flintshire CH5 3LH (GB). **PEAKER, Martin** [GB/GB]; 8 Wood Lea Avenue, Upton-by-Chester, Chester CH2 1NE (GB).


(74) Agent: **BARKER BRETTELL**; 138 Hagley Road, Edgbaston, Birmingham B16 9PW (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European

[Continued on next page]

(54) Title: **VEHICLE SUSPENSION BEAM**



(57) Abstract: A hollow vehicle suspension beam (1) has opposed side walls formed with recesses (11) in which an axle wrap (2) is located and secured by welded jointing (12, 13) internally and externally of the opposed side walls to provide a strong joint between the beam and axle wrap. The beam may comprise at least one component (5, 6) of a generally U-shaped section the opposed limbs of which provide at least part of the opposed side walls of the beam, and the mouth of the section provides an access opening into the interior of the beam for the internal welded jointing (12) to be made at the axle wrap. One embodiment has the beam comprised of two of the U-shaped components (5, 6) disposed with their mouths opening in opposite directions to provide access to the interior of the beam for the internal welded jointing to be made at the axle wrap (2) before the mouths are closed by closure components (15, 16). Another embodiment has the opposed side walls formed in combination by the opposed limbs of a U-shaped component and the space between the plate components being closed off by closure components after the internal welded joint have been made.

WO 02/20288 A1

BEST AVAILABLE COPY



patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Vehicle Suspension Beam

This invention relates to a vehicle suspension beam of the kind which is pivoted at one end to a support for use, carries spring means at or
5 towards its opposite end and has an axle connected to it at an intermediate part of its length.

Suspension beams are known which are of a box-section fabricated from metal plate. Such a beam has an axle wrap, by which the axle is retained
10 to the beam, secured transversely of its length in complementary recesses formed in the beam. The axle wrap is secured to the beam by welded or adhesive jointing at the exterior of the beam. A problem experienced with this known form of suspension beam is that the welded jointing becomes weakened by metal fatigue and can fail under loading to which
15 the axle and beam are subjected in use.

The present invention is aimed at providing a vehicle suspension beam which has a stronger joint between the beam and an axle wrap.

20 According to the present invention a vehicle suspension beam is provided which is hollow and has opposed side walls formed with recesses in which an axle wrap is located and secured to the beam by welded jointing internally and externally of said side walls.

25 At least adjacent to the recesses the beam may be constructed so as to provide an access opening or openings for access into the interior of the beam for the welded jointing to be made between the axle wrap and the opposed side walls. The access opening or openings may be closed subsequently. The beam may, for example, have the or each access
30 opening between the side walls. The beam may comprise at least one component of a generally U-shaped section of which the opposed limbs

provide at least parts of the side walls and the mouth provides an access opening to the interior of the beam. A closure component may be secured to the U-shaped component to close the mouth when the welded jointing has been made internally of the side walls. There may be such a

5 U-shaped component which extends substantially to one side of the axle wrap to provide part of the side walls of the beam, and laterally spaced plate components extending substantially to an opposite side of the axle wrap which provide further parts of the side walls of the beam. Access to the interior of the beam for the welded jointing internally of the side

10 walls may be made by way of the mouth of the U-shaped component and by way of the space between the plate components. The mouth and said space may be closed off subsequently by closure components fixed, for example by welding, to the U-shaped component and the plate components. In another construction the beam, at least adjacent to the

15 recesses, may have components of a generally U-shaped section mouths of which provide access openings which open in opposite directions transversely of the beam and provide access to the interior of the beam for the welded jointing of the axle wrap to the side walls at the interior of the beam to be made. In whichever manner an access opening or

20 openings may be provided it is preferably possible for a continuous welded joint to be made around the circumference of the axle wrap contained inside the beam.

In one embodiment the beam comprises two elongate components of a

25 generally U-shaped section connected end-to-end such that the mouth of the U-shaped section of one component is oppositely directed to that of the other component. The opposed limbs of the U-shaped sections of the components form side walls of the beam. The recesses for the axle wrap are formed in at least one of the components at or adjacent to the end-to-

30 end connection. Access is provided through the mouths of the components for the welded jointing of the axle wrap to the side walls of

the beam at the interior of the beam. The mouths are subsequently closed by closure plates. In another embodiment the beam comprises one such elongate component of a generally U-shaped section and two laterally spaced side plate components which are connected end-to-end with, as
5 continuations of, the opposed limbs of the U-shaped component. The opposed limbs of the U-shaped component and the side plate components form side walls of the beam. The recesses for the axle wrap are formed in the U-shaped component and/or the side plate components at or adjacent to the connection of the side plate components to the limbs of the
10 U-shaped component. Cover plates are secured over the mouth of the U-shaped component and between the side plate components when the welded jointing at the interior of the beam has been made, so as to close off the interior of the beam. The finished beam has a closed box-section. A cover plate which closes the mouth of the U-shaped component may
15 also extend over and be secured to adjacent longitudinal edges of the side plate components.

The axle wrap may be secured to the beam such that part of its length is fully contained inside the beam. Alternatively, for part of its length, a
20 portion of the circumference of the axle wrap may be contained inside the beam and the remainder of the circumference at that part of the length of the axle wrap may be exposed outside the beam. The recesses in the beam are formed accordingly.

25 In the embodiments described the recesses are partially formed in the components at the ends of the components at which they are connected together.

A shear plate or plates may be secured across the interior of the beam for
30 increased transverse rigidity of the beam's section, if required.

A suspension beam in accordance with the present invention has a substantially stronger connection between the beam and axle wrap as a result of the internal and external welded jointing at the side walls of the beam, than has been possible with the known suspension beams which have only external welding jointing at the beam to the axle wrap. The internal and external welded jointing eliminates the failure-promoting relative bending which has occurred at the root of the conventional, external only, welded joint between the beam and axle wrap under loading on the suspension beam when in use. Loading is concentrated instead on the parent material of the structure of the beam.

An embodiment of the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

Figure 1 is a plan view of a suspension beam in accordance with the present invention,

Figure 2 is a side view of the suspension beam,

Figure 3 is an exploded perspective view of the suspension beam, and

Figure 4 is an enlarged detailed section through the suspension beam.

25

The suspension beam of this embodiment is provided for a trailing arm suspension of a trailer vehicle.

The suspension beam comprises a beam proper 1 and an axle wrap 2 secured transversely to the beam 1 at an intermediate part of the length of the beam. In use, as shown in Figure 2, a pivot bush 3 is secured to a

front end of the beam 1, an air spring, not shown, is mounted on a seating 4 provided on the rearward end part of the beam, and the axle wrap 2 is secured on an axle A.

- 5 As best seen in Figure 3, the beam 1 comprises two elongate, forward and rearward, components 5, 6 which are each of a generally U-shaped section and are butt-welded end-to-end. Each component 5, 6 is made from metal plate cut to the required outline and formed to the generally U-shaped section. Opposed side limbs 5' 6' and the web 5" 6" of the
- 10 section of each of the two components 5, 6 are straight and meet at right angles to form three sides of a box-section. The side limbs 5' of the forward component converge towards the front end of the beam, whereas the side limbs 6' of the rearward component run substantially in parallel to the rear end of the beam. At their butting ends the two components are
- 15 welded together at their side limbs 5', 6' which form side walls of the beam. They are welded such that the web 5" of the forward component 5 is at the top of the beam and the web 6" of the rearward component 6 is at the bottom of the beam. Mouths 7, 8 of the U-shaped sections of the forward and rearward components are thus respectively at the bottom and
- 20 the top of the beam, and provide access into the interior of the beam at the two components. Part of the web 5" of the forward component is cut away adjacent to the rearward component to provide an extension 8' of the mouth 8 of the rearward component into the forward component.
- 25 Side limbs 5' of the forward component 5 taper gradually towards the front of the beam. The side limbs 6' of the rearward component 6 are of similar height to those of the forward component at the butting ends of the components but then taper to approximately half that height and continue at the reduced height, with a gradual taper, for the greater part
- 30 of the length of the component extending to the rear of the beam.

Part-circular hollows 9, 10 are formed in the edges of the side limbs 5', 6' at the butting ends of the two components 5, 6. With the components welded together, the hollows 9, 10 in their aligned side limbs register to define together an almost circular recess 11 at each side of the beam.

- 5 The two recesses 11 are co-axial and of a complementary diameter to receive the axle wrap 2 as a close fit. The hollows 9 in end edges of the side limbs 5' of the forward component are adjacent to the mouth 7 of the section of that component, and the hollows 10 in the end edges of the side limbs 6' of the rearward component are adjacent to the web 6" of the
- 10 section of the rearward component. The two recesses 11 open for a short arcuate distance, of less than one quarter of their circumferences, through the bottom of the beam.

- The axle wrap 2, which is tubular and formed from two similar semi-cylindrical metal shells welded together, is located in the co-axial
- 15 recesses 11 and projects from each side of the beam, Figure 1. It is secured to the beam at the side limbs of the forward and rearward components by continuous welding 12, 13 around the edges of the hollows 9, 10 on the inside, Figure 4, and the outside surfaces, Figure 2, of the
- 20 side limbs. Access for the welding to be done at the inside surfaces is gained through the mouths 7, 8 of the U-shaped sections of the two components. The mouths allow sufficient access for continuous welding to be done all around the perimeter of each recess at the inside surfaces of the respective side limbs.

25

The axle wrap may also be welded to the adjacent edge of the web 6" of the rearward component 6.

- A stiffening shear plate 14 is secured across the interior of the beam in
- 30 the forward component 5 above and generally radial to the axle wrap.

The shear plate extends between and is welded to the side limbs 5' of the forward component.

Once the axle wrap 2 and shear plate 14 have been welded in place a forward cover plate 15 is welded in the mouth 7 of the forward component to close the bottom of the beam between its front end and the axle wrap. The cover plate 15 may be welded to the axle wrap as well. A rearward cover plate 16 is welded over the mouth 8 of the rearward component and the extension 8' in the forward component to close the top of the beam between its rear end and the web 5" of the forward component. This further cover plate 16 provides the seating 4 on the beam for the air spring.

Front ends 17, 18 of the web 5" of the forward component and of the forward cover plate 15 and front edges of the side limbs 5' of the component are so shaped as to form in combination a seating 19 to hold the pivot bush 3.

CLAIMS

1. A vehicle suspension beam which is hollow and characterised in that it has opposed side walls formed with recesses (11) in which an axle
5 wrap (2) is located and secured to the beam (1) by welded jointing (12, 13) internally and externally of said side walls.
2. A vehicle suspension beam according to claim 1 characterised in that at least adjacent to the recesses (11) the beam (1) is constructed so as
10 to provide an access opening or openings (7, 8) for access into the interior of the beam for the internal welded jointing (12) to be made between the axle wrap and the opposed side walls.
3. A vehicle suspension beam according to claim 2 characterised in
15 that the or each access opening (7, 8) is closed after the internal welded jointing (12) has been made.
4. A vehicle suspension beam according to claim 2 or claim 3 characterised in that the beam (1) has the or each access opening (7, 8)
20 between the opposed side walls.
5. A vehicle suspension beam according to claim 4 characterised in that the beam (1) comprises at least one component (5, 6) of a generally U-shaped section of which the opposed limbs (5', 6') provide at least parts
25 of the opposed side walls and the mouth (7, 8) provides an access opening to the interior of the beam.
6. A vehicle suspension beam according to claim 5 as dependent from claim 3 characterised in that a closure component (15, 16) is secured to
30 the U-shaped component (5, 6) to close the mouth (7, 8) when the internal welded jointing (12) has been made at the opposed side walls.

7. A vehicle suspension beam according to claim 5 or claim 6 characterised in that the U-shaped component extends substantially to one side of the axle wrap (2) to provide part of the opposed side walls of the beam, and laterally spaced plate components extend substantially to an opposite side of the axle wrap to provide further parts of the opposed side walls of the beam, access to the interior of the beam for the internal welded jointing at the opposed side walls being made by way of the mouth of the U-shaped component and by way of the space between the plate components.

8. A vehicle suspension beam according to claim 7 as dependent from claim 6 characterised in that the space between the plate components is closed off after the internal welded jointing (12) has been made at the opposed side walls by closure components fixed to the plate components.

9. A vehicle suspension beam according to claim 5 or claim 6 characterised in that at least adjacent to the recesses (11) the beam (1) comprises two of the components (5, 6) of generally U-shaped section mouths (7, 8) of which provide access openings opening in opposite directions transversely of the beam to provide access to the interior of the beam for the internal welded jointing (12) of the axle wrap (2) to the opposed side walls of the beam to be made.






10. A vehicle suspension beam according to any preceding claim characterised in that the internal welded jointing at the opposed side walls is continuous around the circumference of the axle wrap (2).

11. A vehicle suspension beam according to any preceding claim characterised in that the axle wrap (2) is secured to the beam (1) such that part of its length is fully contained inside the beam.

12. A vehicle suspension beam according to any of claims 1 to 10 characterised in that for part of its length a portion of the circumference of the axle wrap (2) is contained inside the beam (1) and the remainder of
5 the circumference at that part of the length of the axle wrap is exposed outside the beam.

13. A vehicle suspension beam according to any preceding claim characterised in that one or more shear plates (14) are secured across the
10 interior of the beam (1) to provide increased transverse rigidity of the beam's section.

1/1



BEST AVAILABLE COPY

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B60G7/00 B60G7/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B60G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 600 198 A (BOLER CO) 8 June 1994 (1994-06-08) column 11, line 46 -column 12, line 2; figures 11-15 column 9, line 30 - line 36 ---	1,5,6,11
A	US 5 375 871 A (KLEIN JASON M ET AL) 27 December 1994 (1994-12-27) column 5, line 13 -column 6, line 3; figures ---	1,5-7,9, 12,13
A	WO 00 01548 A (BOLER CO) 13 January 2000 (2000-01-13) page 13, line 17 - line 29; figures 3,4,8-10 page 11, line 26 - line 30 ---	1,2
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

9 January 2002

Date of mailing of the international search report

16/01/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Torsius, A

INTERNATIONAL SEARCH REPORT

Inter. Appl. No.

PCT/GB 01/03895

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 196 38 082 C (SAUER ACHSENFAB) 5 February 1998 (1998-02-05) column 2, line 4 - line 26; figure abstract	1,5,6,12
A	US 4 512 559 A (AOYAMA SHIGETSUNE ET AL) 23 April 1985 (1985-04-23) column 13, line 38 - line 39; figure 32	1

BEST AVAILABLE COPY

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0600198	A	08-06-1994	AT 171422 T	15-10-1998
			AU 666572 B2	15-02-1996
			AU 4614293 A	05-05-1994
			BR 9304278 A	26-04-1994
			CA 2108724 A1	20-04-1994
			DE 69321199 D1	29-10-1998
			DE 69321199 T2	27-05-1999
			DK 600198 T3	14-06-1999
			EP 0600198 A2	08-06-1994
			EP 0863060 A2	09-09-1998
			ES 2121909 T3	16-12-1998
			KR 9700623 B1	16-01-1997
			US 5366237 A	22-11-1994
US 5375871	A	27-12-1994	NONE	
WO 0001548	A	13-01-2000	AU 9672798 A	24-01-2000
			BR 9815925 A	20-02-2001
			EP 1089889 A1	11-04-2001
			WO 0001548 A1	13-01-2000
			US 2001020775 A1	13-09-2001
DE 19638082	C	05-02-1998	DE 19638082 C1	05-02-1998
			EP 0830960 A2	25-03-1998
US 4512559	A	23-04-1985	JP 1212588 C	12-06-1984
			JP 57009339 A	18-01-1982
			JP 58047581 B	24-10-1983

BEST AVAILABLE COPY